

TR


CRU Dikey Atışlı Çatı Tipi Radyal Fanlar

Genel Özellikler

- 12.000m³/h kapasiteye kadar üretimi yapılabilir.
- Maksimum verimlilikte radyal geri eğik kanatlara sahiptir.
- Gövde sert çelikten imal edilmekte ve standart olarak elektrostatik toz boya ile kaplanmaktadır.
- Yağmur suyu ve kar gibi etkenlere karşı dayanımlıdır. Dış ortam şartlarında çalışmaya uygundur.
- IP 54 motor koruması mevcuttur.
- Tüm modellerde hız kontrolü yapılabilir.
- +50°C sıcaklıkta daimi çalışmaya uygundur.

Kullanım Alanları

- Genel mahal havalandırmaları
- Filtre sistemi ile birlikte mutfak davlumbaz egzozları
- Ofis, restoran, garaj, depo ve atölye havalandırmaları

**EN**

CRU Vertical Outlet Centrifugal Roof Type Fan

General Features

- It can be produced up to 12.000m³/h capacity.
- It has radial backward curved blades with maximum efficiency.
- The fan casing is made of hard steel and it is coated electrostatic powder coating as standart.
- It is resistant to factors such as rainwater and snow. It is suitable to work in outdoor conditions.
- IP 54 motor protection is available.
- Speed control can be done in all models.
- Suitable for continuously operation at +50°C.

Areas of Usage

- General area ventilation
- Kitchen hood exhausts with filter system
- Office, restaurant, garage, warehouse and workshop ventilation



Genel Özellikler / General Features

MODEL	m ³ /h	V-50Hz	MOTOR			Statik Basınç Performans Tablosu (Pst/Pa)										SPL dB(A)
			(kW)	(rpm)	(A)	50	100	150	200	250	300	400	500	600	750	
CRU 20-2M	1100	230V-50Hz	0,14	2600	0,60	1000	960	900	820	760	700	480				56
CRU 25-2M	1450	230V-50Hz	0,20	2600	1,05	1400	1330	1220	1110	1010	900	600	300			57
CRU 28-2M	1900	230V-50Hz	0,24	2500	1,10	1900	1880	1850	1800	1700	1550	1100	600			59
CRU 31-4M	2550	230V-50Hz	0,21	1400	1,00	2400	2300	2000	1600	1300	1000					60
CRU 35-4M	3300	230V-50Hz	0,40	1400	1,20	3100	2900	2700	2400	2000	1800	1300				62
CRU 40-4M	4400	230V-50Hz	0,51	1380	1,50	4100	3900	3800	3500	3300	3100	2400	1800			66
CRU 45-4M	5800	230V-50Hz	0,80	1350	2,50	5600	5300	5000	4600	4300	4000	3000	2000			68
CRU 50-4T	9500	400V-50Hz	1,50	1400	2,60	9200	9000	8700	8300	8000	7500	6600	5400			76
CRU 56-4T	12000	400V-50Hz	1,80	1340	4,50	12000	11900	11800	11600	11400	11200	10400	9500	8200	6000	79

Ölçüler / Dimensions

MODEL	A	B	C	D
CRU 20-2M	380	350	300	25
CRU 25-2M	400	280	320	25
CRU 28-2M	400	280	320	25
CRU 31-4M	565	370	485	30
CRU 35-4M	565	370	485	30
CRU 40-4M	565	470	485	30
CRU 45-4M	620	550	540	30
CRU 50-4T	700	570	620	40
CRU 56-4T	830	600	750	40

